

Type [↵]			
Structure type [↵]	UOO [↵]	UUT [↵]	UOT [↵]
Function [↵]	Position, speed, sway [↵]		
Load size [↵]	400*400*400~ [↵] 700*700*700 [↵]	φ300mm~φ580mm [↵]	
Countertop material [↵]	Stainless steel / aluminum alloy [↵]		
Carrying capacity [↵]	40kg~100kg [↵]		≥50kg [↵]
Rate range [↵]	±0.001°/s~±800°/s [↵] ±0.001°/s~±400°/s [↵] ±0.001°/s~±200°/s [↵]		
Angular rate accuracy [↵] And rate smoothness [↵]	2 × 10 ⁻⁵ (360 ° average) [↵] 2 × 10 ⁻⁴ (10 ° average) [↵] 2 × 10 ⁻³ (1 ° average) [↵]		
Single-axis turntable angle [↵] Position accuracy parameter [↵]	±2" (I) , ±5" (II) , ±15"(III) [↵]		
Position measurement repeatability [↵]	±1" [↵]		
Position measurement resolution [↵]	0.36" [↵]		
Angular position range [↵]	Three-axis continuous infinite [↵]		
Display range	0°~359.9999° [↵]		
Angular acceleration [↵]	customized [↵]		
User slip ring	customized [↵]		